

ILS Platform Series

Capture Larger Opportunities

The ILS series are our largest and most sophisticated laser platforms, ideal for businesses that process large objects. The ILS laser platforms feature work areas up to twice as large as the largest PLS or VLS laser platforms, and a patented, true Class IV pass-through mode is available for safe processing of objects of unlimited length. Factory ready features like the automation interface allow a properly configured ILS laser platform to serve as either a standalone production solution or be an integrated component of an automated assembly line.



Laser Technology Benefits

- ▶ **Software Controlled** - The laser can be controlled by any software with a print function.
- ▶ **Multi-Material** - Process an endless number of materials available today and in the future.
- ▶ **Multi-Process** - Cut, engrave, mark, and produce photo images in one step.
- ▶ **Non Contact** - Modify material without applying any physical force.
- ▶ **On Demand** - Produce everything you need in real time, without waiting for hard tooling.

Uniquely Universal Features

- ▶ **ULR Laser Sources**
Universal's patented air-cooled free-space gas slab lasers produce an excellent quality beam with even power distribution and good near- and far-field characteristics, making them ideal for laser material processing.
- ▶ **High Power Density Focusing Optics™**
High Power Density Focusing Optics (HPDFO) allow the laser beam to be focused to a much smaller spot, making it possible to engrave smaller text and produce sharper images at tighter tolerances.
- ▶ **1-Touch Laser Photo™**
1-Touch Laser Photo is a proprietary software package that makes it quick and easy to produce photographic images on nearly any material.
- ▶ **SuperSpeed™**
SuperSpeed is suitable for raster image applications and requires Dual Laser Configuration. This component allows two lines of a raster image to be produced simultaneously. For vector cutting, the laser beams can be combined to take advantage of higher power.
- ▶ **Rapid Reconfiguration™ of Lasers**
Laser platforms with Rapid Reconfiguration can be reconfigured with new laser sources in seconds, without tools. This allows you to configure your laser system to suit the task at hand, increasing quality and throughput.
- ▶ **Laser Interface+™**
This materials-based driver automatically determines the optimum processing settings for your target material. Just select the material type, enter in the material thickness, and start the laser system.
- ▶ **Dual Laser Configuration**
The Dual Laser Configuration optically combines two ULS laser sources into a single beam for additional power and flexibility.
- ▶ **Pass-Through**
When used in conjunction with an approved work environment, our large-format ILS laser platforms can be configured to allow processing of items of unlimited length in full compliance with Class IV laser safety regulations.

System Specifications

	ILS9.75	ILS12.75
▶ Work Surface Area¹	36 x 24 in (914 x 610 mm)	48 x 24 in (1219 x 610 mm)
▶ Maximum Part Size²	40.5 x 30 x 12 in (1029 x 762 x 305 mm)	52.5 x 30 x 12 in (1334 x 762 x 305 mm)
▶ Dimensions	57 x 44 x 46 in (1448 x 1118 x 1168 mm)	69 x 44 x 46 in (1753 x 1118 x 1168 mm)
▶ Rotary Capacity	Max Diameter 10.25 in (260 mm)	
▶ Motorized Z Axis Lifting Capacity	60 lbs (27 kg)	
▶ Pass-Through Class 4 Mode Accessible Work Area	20 x ∞ in (508 x ∞ mm)	
▶ Pass-Through Class 4 Mode Clearance	23.75 x 8 in (603 x 203 mm)	
▶ Available Focus Lenses	2.0 in (51 mm) *standard	3.0 in (76 mm)
▶ Laser Platform Interface Panel	Keypad and LCD display shows current file name, laser power, engraving speed, PPI and run time	
▶ Operating System Compatibility	Requires a dedicated PC to operate. Compatible with Windows XP/Vista/7 – 32/64 bit	
▶ PC Connection	USB 2.0	
▶ Cabinet Style	Floor Standing	
▶ Optics Protection	Plumbed for compressed-air-based optics protection	
▶ Laser Options	10, 25, 30, 40, 50, 60, 75 Watts. Dual Laser Configuration Optional	
▶ Approximate Weight	400 lbs (181 kg)	430 lbs (195 kg)
▶ Power Requirements	220V-240V/10A (1 laser) 220-240V/16A (2 lasers)	
▶ Exhaust Connection	Two 4 in (102 mm) ports 700 CFM @ 6 in static pressure (1190 m ³ /hr at 1.5 kPa)	Two 4 in (102 mm) ports 1000 CFM @ 6 in static pressure (1700 m ³ /hr at 1.5 kPa)

USA

7845 E. Paradise Lane
Scottsdale, AZ 85260

+1 480-483-1214
moreinfo@ulsinc.com

Japan

The Yokohama Landmark Tower
15th Fl. 2-2-1-1 Minato Mirai
Nishi-ku Yokohama-shi
Kanagawa-ken 220-8115 JAPAN

+81 45-224-2270
japansales@ulsinc.com

Europe

Lerchenfelder Gürtel 43
1160 Vienna, Austria

+43 1-402-22-50
eurosales@ulsinc.com

UNIVERSAL[®]
LASER SYSTEMS

Learn more at ulsinc.com



CDRH Class 1 safety enclosure for CO₂ laser³. Class 3R for red laser pointer.



¹ Work area varies by speeds and throughput

² Maximum part size defined as used with 1.5 lens

³ CDRH Class 1 laser safety enclosure provides for safe operation without the need for an interlocked room or protective eyewear.

WARNING: UNIVERSAL LASER SYSTEMS PRODUCTS ARE NOT DESIGNED, TESTED, INTENDED OR AUTHORIZED FOR USE IN ANY MEDICAL APPLICATIONS, SURGICAL APPLICATIONS, MEDICAL DEVICE MANUFACTURING, OR ANY SIMILAR PROCEDURE OR PROCESS REQUIRING APPROVAL, TESTING, OR CERTIFICATION BY THE UNITED STATES FOOD AND DRUG ADMINISTRATION OR OTHER SIMILAR GOVERNMENTAL ENTITIES. FOR FURTHER INFORMATION REGARDING THIS WARNING CONTACT UNIVERSAL LASER SYSTEMS OR VISIT WWW.ULSINC.COM.

Manufactured and protected under one or more U.S. Patents: 5,661,746; 5,754,575; 5,867,517; 5,881,087; 5,894,493; 5,901,167; 5,982,803; 6,181,719; 6,313,433; 6,342,687; 6,423,925; 6,424,670; 6,983,001; 7,060,934; D517,474. Other U.S. and international patents pending.

©2011 Universal Laser Systems, Inc. All rights reserved. Universal Laser Systems logo and name are registered trademarks, and Rapid Reconfiguration, Laser Interface+, 1-Touch Laser Photo, SuperSpeed and High Power Density Focusing Optics (HPDFO) are trademarks of Universal Laser Systems, Inc. All other company and product names are trademarks or registered trademarks of their respective companies.

MCO38-110411
CPT REV 0112